

METHOD AND DEVICE FOR ADMINISTERING A MULTIPLICITY OF  
TERMINALS

CLAIM FOR PRIORITY

5           This application claims priority to European  
Patent Application No. 00117011.7 filed on August 8,  
2000, the disclosure of which is incorporated by  
reference in its entirety.

10   Technical Field of the Invention

          The invention relates to a central entity for  
administering terminals of a user, and in particular,  
to information regarding which applications and  
terminal can interact with one another and the methods  
15 of information exchange.

Background of the Invention

          The interest of commercial information  
providers, usually also called service providers, in  
20 data networks such as the Internet has risen  
dramatically in recent years. This development is  
primarily due to the flexibility of the exchange of  
information and the comparably low costs. Thus, for  
example, it is very simple in the Internet to provide  
25 information quickly and inexpensively worldwide, or  
even to offer completely new services, without  
interposing a central entity. This is based on the  
distributed communication architecture of the Internet.  
However, it is very difficult to enforce uniform  
30 guidelines in this type of arrangement.

          As data and telephone networks become fused  
together, a multiplicity of new terminals are suddenly  
invading the telecommunication market. Examples of this  
are the WAP (Wireless Access Protocol) terminals which  
35 have already been introduced. The continuously  
increasing demand for greater bandwidths also provides  
for more and more services, for example also  
increasingly in the multimedia field.

5

10

15

20

## Summary of the Invention

25

30

35

In yet another aspect of the invention, the method for administering terminals in communication networks includes, for example, performing the inquiry for the user of the terminals by the application, and supplying  
5 a list of terminals allocated to the user back to the application.

In still another aspect of the invention, an interrogation is permitted if the application has authority for the interrogation.

10 In one aspect of the invention, in the registration information, preferences relating to the terminals are specified, for example, an order of priority in which individual terminals are to be addressed, data formats to transmit voice and/or data  
15 to the corresponding terminal, and transmission standards for the transmission.

In another aspect of the invention, the application decides from the registration information supplied back which terminal establishes contact.

20 In yet another aspect of the invention, the application establishes contact with a number of terminals.

In another embodiment of the invention, there is a device for administering terminals in communication  
25 networks which includes, for example, at least one terminal registered with a central registration entity, and at least one application to communicate with the at least one terminal, the application performs an inquiry at the central registration entity, and the  
30 application performs at least one action on the basis of the result of the inquiry.

In one aspect of the invention, the registering of the terminal with the central registration entity is not carried out by the terminal to be registered.

35 In another aspect of the invention, the registration information is updated.

In yet another aspect of the invention, the application performs the inquiry for the user of the

terminals, and supplying a list of terminals is allocated to the user is supplied back to the application.

5 In still another aspect of the invention, an interrogation is permitted if the application has authority for the interrogation.

10 In one aspect of the invention, in the registration information, preferences relating to the terminals are specified as an order of priority in which individual terminals are to be addressed, data formats to transmit voice and/or data to the corresponding terminal, and transmission standards for the transmission.

15 In another aspect of the invention, the application decides from the registration information supplied back which terminal establishes contact.

In still another aspect of the invention, the application establishes contact with a number of terminals.

20

#### Brief Description of the Drawings

In the text which follows, the invention will be explained with reference to exemplary embodiments. In the figures:

25 Figure 1 shows the system architecture for the central administration of terminals.

Figure 2 shows a message flow by way of example.

30 Figure 3 shows an exemplary embodiment of a user who uses two terminals and has subscribed to two services.

#### Detailed Description of the Preferred Embodiments

35 The invention enables a user to have a multiplicity of terminals, of different types, and for each to intercommunicate with the application within its capabilities.

In one embodiment, there is a central entity for administering terminals of a user. The terminals of

the respective user register with this entity and leave information on the manner in which applications can interact with them and which methods of information exchange are supported by them (protocols, data  
5 exchange formats, address information).

Applications initiating an interaction with terminals inquire at the central entity via which terminals a certain user can be reached. As a result of the inquiry, the application (if it is authorized to  
10 receive this information) receives a list of the terminals of the user. This list includes address information and information on possible data exchange formats and protocols supported by the terminal for each terminal.

15 When a user uses a multiplicity of terminals and applications, certain characteristics (descriptions) of these terminals are administered by a central entity. Terminals register their address information and information on possible data exchange  
20 formats and protocols at the central entity, and keep this registration information updated.

Applications which intend to contact a user obtain information about the registered terminals of this user from the central entity.

25 Instead of terminals, other network elements can also handle the registration.

In mobile terminals, the position in a network (address) can vary with time and the access technology can also change when roaming into other network  
30 segments. Hence, registered information can also change dynamically. Thus, terminals need to keep their registration information updated.

On the basis of the information signaled back from the central entity, the application can decide  
35 whether and by which way it wants to contact the user in question. It selects the terminals in question in accordance with a suitable algorithm and addresses them. The algorithm can also take into consideration

settings by the user. These settings are also administered by the central entity and supplied to the applications.

Advantages of a central administration of  
5 terminals:

If there is no central administration of terminals, terminals will always have to register with all applications in question. This is very expensive since the number of applications to which a user has  
10 subscribed can be very large. These registration mechanisms would have to be set up on every terminal of the user. In addition, each application provider would also have to implement mechanisms for registration which may be different for each type of terminal.

In the case of central administration, the  
15 central entity implements the registration interfaces. Terminals register precisely at this central entity known to them. At the same time, applications only need to support the interface to the central entity which  
20 can also be easily standardized.

In addition, preferences (e.g. in accordance with aspects of cost relating to the terminals with which the application is to communicate, can also be set up at the central administration (e.g. selection or  
25 order of priority of the terminals, preferred data formats and transmission standards).

Figure 1 describes the system architecture for the central administration of terminals. It shows the central entity which can be located in any network, for  
30 example the Internet. Terminals A, B, C can register with the entity by means of a registration process, or also deregister. The applications 1, 2 can interrogate information on the registered terminals, for use with the application, from the central entity and then  
35 receive back, for example, a list of the registered terminals of a user, depending on the type of application.

Figure 2 shows an exemplary flow of messages between the central entity and the terminals, on the one hand, and the applications (for example services), on the other hand. The terminals register in a suitable manner at a central administration entity, for example with the type of terminal, the type of communication possible with this terminal, and other information. The registration can take place from the terminal itself or by a third entity.

As soon as an application (for example a service) requires information on terminals, it can interrogate the central entity for this information.

Figure 3 represents an exemplary application. A user N has a mobile telephone (terminal A from figure 1) which supports the short message service SMS (application 1), and a normal landline telephone (terminal B). The user N also uses a calendar application appointments calendar (application 2) in which he has entered at least one appointment.

The user N (or his/her mobile telephone, landline telephone terminals, respectively) are active and have registered with the central entity according to the invention in the network, Internet. This is stored, for example, in a table T and other solutions such as databases are known to the expert.

The calendar application monitors appointments and reminder times and informs the user N about when the appointment in question has approached. For this purpose, the application contacts the user.

The application then turns to the central entity 1 and obtains a list of terminals at which it can reach the user 2. From the list of terminals, the application determines which two terminals are registered. One is a mobile telephone which can be activated via the SMS or a voice link and the other one is a landline telephone for which a voice link can be used. In addition, the user can previously set his/her

preference between the short message service or a voice message at the mobile terminal.

5 In the example, the application is configured in such a way that it notifies the user in different ways. Thus, it sends the appointment information as a short message to the address of the mobile terminal, 3a, and, in parallel, sets up a telephone link to the landline telephone of the user, 3b, in order to announce to him/her the appointment information.

09023800-080801